

Traglasten mit Ballast 2 t

360°

Werte in () gelten für Abstützung 50% ausgefahren. DIN 75%

Ausladung Radius [m]	Auslegerlänge / boom length in [m]						
	9	12,5	16	19,5	23	26,5	30
1,0	35,0 (35,0)	20,0 (20,0)	15,0 (15,0)	14,0 (14,0)			
2,0	35,0 (35,0)	20,0 (20,0)	15,0 (15,0)	14,0 (14,0)	11,0 (11,0)	8,9 (8,9)	
3,0	29,4 (27,5)	20,0 (20,0)	15,0 (15,0)	14,0 (14,0)	11,0 (11,0)	8,9 (8,9)	5,0 (5,0)
4,0	24,3 (22,3)	20,0 (20,0)	15,0 (15,0)	14,0 (14,0)	11,0 (11,0)	8,9 (8,9)	5,0 (5,0)
5,0	20,6 (15,7)	20,0 (15,5)	15,0 (15,0)	13,3 (13,3)	11,0 (10,8)	8,6 (8,6)	5,0 (5,0)
6,0	17,1 (11,2)	17,7 (11,1)	14,9 (10,9)	12,0 (11,5)	10,3 (10,3)	8,3 (8,3)	5,0 (5,0)
7,0		14,3 (8,4)	13,2 (8,3)	10,9 (8,7)	9,5 (9,1)	7,8 (7,8)	5,0 (5,0)
8,0		11,2 (6,6)	11,1 (6,5)	9,8 (6,9)	8,7 (7,2)	7,4 (7,4)	5,0 (5,0)
9,0		9,0 (5,3)	8,9 (5,2)	9,0 (5,6)	7,9 (5,9)	6,9 (6,1)	5,0 (5,0)
10,0			7,3 (4,2)	7,9 (4,6)	7,1 (4,9)	6,4 (5,1)	5,0 (5,0)
11,0			6,1 (3,4)	6,6 (3,8)	6,5 (4,1)	5,9 (4,3)	5,0 (4,5)
12,0			5,2 (2,8)	5,6 (3,2)	5,9 (3,5)	5,5 (3,7)	5,0 (3,8)
13,0				4,8 (2,7)	5,2 (3,0)	5,1 (3,1)	4,7 (3,3)
14,0				4,2 (2,3)	4,5 (2,5)	4,7 (2,7)	4,4 (2,8)
15,0				3,6 (1,9)	3,9 (2,2)	4,1 (2,3)	4,1 (2,5)
16,0				3,2 (1,6)	3,4 (1,8)	3,7 (2,0)	3,8 (2,2)
17,0					3,0 (1,6)	3,2 (1,7)	3,4 (1,9)
18,0					2,7 (1,3)	2,9 (1,5)	3,0 (1,6)
19,0					2,4 (1,1)	2,6 (1,3)	2,7 (1,4)
20,0					2,1 (0,9)	2,3 (1,1)	2,4 (1,2)
21,0						2,0 (0,9)	2,2 (1,1)
22,0						1,8 (0,8)	1,9 (0,9)
23,0							1,7 (0,8)
24,0							1,5 (0,6)
25,0							1,4 (0,5)
26,0							1,2 (0,4)

630TM-30.0/75/2811/2/06.00 (630TM-30.0/75/2010/2/09.00)